

GDY434CF



SEAMLESS KNITTED CUT-RESISTANT GLOVE WITH BI-POLYMER COATING WITH SANDY FINISH AND OPEN FINGERTIPS

DESCRIPTION

- > K3 Knitting Technology: unmatched dexterity and flexibility, without compromising on protection
- > HPPE interior to ensure the best level of comfort during use
- > Special bipolymer coating for a perfect balance between mechanical wearing resistance and flexibility
- > Micro-porous nitrile coating, not in contact with the user's skin, for maximum breathability and grip in dry environment
- > Contact heat resistance 1 (100 °C for at least 15 seconds)

APPLICATION

- > Precision handling of sharp and abrasive pieces

CAT	CAT.II
Environment	Dry or slightly wet/oily
Construction	Seamless knitted
Coating area	Palm
Length (mm)	220-270
Cuff type	Elasticized knitted wrist
Ambidextrous	No
Size	6-11
Packing	Sales Units: 12 PA



MECHANICAL PROTECTION

EN388



4342B



Release 22/03/2024

REGISTRATED TRADEMARK SAFETY SYSTEM
(DEP.NUM. 302017000074272)



Lanzi SRL Via Giulio Natta, 27/A Torino - Italia
Tel: +39 011 2284011 - Fax: + 39 011 2884022
contact@lanzigroup.com