

**GT51E**



SEAMLESS KNITTED POLYAMIDE/CARBON GLOVE WITH POLYURETHANE COATING

**DESCRIPTION**

- > High abrasion resistance of the polyurethane coating
- > Guaranteed breathability and grip in dry environment
- > Anti-static according to EN16350 to prevent explosion risks in ATEX environments
- > Anti-static test result:  $4,53 \times 10^5$  Ohms

**APPLICATION**

- > Precision handling of abrasive pieces
- > Suitable for product protection in EPA environments (ESD Protected Area) in the electrical industry and other industries involving electrical components

**MECHANICAL PROTECTION**

EN388



3131X

**ELECTROSTATIC PROTECTION**

EN16350



CAT	CAT.II
Environment	Dry or slightly wet/oily
Construction	Seamless knitted
Gauge	13
Coating area	Palm
Length (mm)	220-260
Cuff type	Elasticized knitted wrist
Ambidextrous	No
Size	6-11
Packing	Sales Units: 12 PA



Release 22/03/2024

REGISTRATED TRADEMARK SAFETY SYSTEM  
(DEP.NUM. 302017000074272)



**Lanzi SRL** Via Giulio Natta, 27/A Torino - Italia  
Tel: +39 011 2284011 - Fax: + 39 011 2884022  
contact@lanzigroup.com