

GPA424



SEAMLESS KNITTED POLYAMIDE/SPANDEX GLOVE WITH NITRILE FOAM COATING WITH SANDY FINISH

DESCRIPTION

- > Elastic shell and ergonomic design for exceptional dexterity and comfort
- > Micro-porous nitrile coating, not in contact with the user's skin, for maximum breathability and grip in dry environment
- > Significantly higher abrasion resistance compared with a smooth nitrile coating
- > Contact heat resistance 1 (100 °C for at least 15 seconds)
- > Available in retail packaging

APPLICATION

- > Precision handling of abrasive pieces, also in presence of light contact heat risk

CAT	CAT.II
Environment	Dry or slightly wet/oily
Construction	Seamless knitted
Gauge	15
Coating area	Palm
Length (mm)	220-260
Cuff type	Elasticized knitted wrist
Ambidextrous	No
Material	Polyamide/spandex
Size	6-10
Packing	Box: 144 PA Sales Units: 12 PA

**MECHANICAL PROTECTION**

EN388



4121X

HEAT AND/OR FIRE PROTECTION

EN407



X1XXXX



Release 21/03/2024

REGISTRATED TRADEMARK SAFETY SYSTEM
(DEP.NUM. 302017000074272)



Lanzi SRL Via Giulio Natta, 27/A Torino - Italia
Tel: +39 011 2284011 - Fax: + 39 011 2884022
contact@lanzigroup.com