GPA428





MECHANICAL PROTECTION



4121X

HEAT AND/OR FIRE PROTECTION EN407



PROTECTION AGAINST PESTICIDES ISO 18889



SEAMLESS KNITTED POLYAMIDE/SPANDEX GLOVE WITH DOUBLE COATING IN SMOOTH NITRILE AND NITRILE FOAM WITH SANDY FINISH

DESCRIPTION

- > For extended handling of oily/greasy parts, with maximum
- levels of comfort and dexterity thanks to the elasticized shell
- > First coating in liquid-proof smooth nitrile
- exceptional grip in oily environment
- > Fully open back to limit sweating even after long usage
- > Significantly higher abrasion resistance compared with a smooth nitrile coating

APPLICATION

> Automotive and mechanical industry for extended handling of oily/greasy parts

> Precision handling of extremely abrasive pieces

CAT	CAT.III
Environment	Dry or moderately wet/oily
Construction	Seamless knitted
Gauge	13
Coating area	Palm
Length (mm)	225-275
Cuff type	Elasticized knitted wrist
Ambidextrous	No
Material	Polyamide/spandex
Coating material	Liquid-proof smooth nitrile and nitrile foam with sandy finish
Size	6-11
Packing	Box: 144 PA Sales Units: 12 PA





Release 21/03/2024

REGISTRATED TRADEMARK SAFETY SYSTEM (DEP.NUM. 302017000074272)





Lanzi SRL Via Giulio Natta, 27/A Torino - Italia Tel: +39 011 2284011 - Fax: + 39 011 2884022 contact@lanzigroup.com

