

GT51E



SEAMLESS KNITTED POLYAMIDE/CARBON GLOVE WITH POLYURETHANE COATING

DESCRIPTION

- > High abrasion resistance of the polyurethane coating
- > Exceptional breathability and grip in dry environment
- > Anti-static according to EN16350 to prevent explosion risks in ATEX environments
- > Anti-static test result: $4,53 \times 10^5$ Ohms

APPLICATION

- > Precision handling of abrasive pieces
- > Suitable for product protection in EPA environments (ESD Protected Area) in the electrical industry and other industries involving electrical components

MECHANICAL PROTECTION

EN388



3131X

ELECTROSTATIC PROTECTION

EN16350



CAT	CAT.II
Environment	Dry or slightly wet/oily
Construction	Seamless knitted
Gauge	13
Coating area	Palm
Length (mm)	220-260
Cuff type	Elasticized knitted wrist
Ambidextrous	No
Size	6-11
Packing	Box: 144 PA Sales Units: 12 PA



Release 21/03/2024

REGISTRATED TRADEMARK SAFETY SYSTEM
(DEP.NUM. 302017000074272)



Lanzi SRL Via Giulio Natta, 27/A Torino - Italia
Tel: +39 011 2284011 - Fax: + 39 011 2884022
contact@lanzigroup.com