

ISO-SKIN GIS884



MECHANICAL PROTECTION

EN388



4X42F

HEAT AND/OR FIRE PROTECTION

EN407:2004



X1XXXX

ELECTROSTATIC PROTECTION

EN16350



SEAMLESS KNITTED CUT-RESISTANT GLOVE WITH HI-FOAM COATING

DESCRIPTION

- > Soft-Shield knitting technology: maximum cut resistance with unmatched dexterity and flexibility
- > HPPE inner plating for excellent comfort
- > Hi-Foam coating for superior breathability and durability
- > Micro-porous coating, not in contact with the user's skin, for maximum grip in dry environment
- > Low-linting coating
- > Anti-static according to EN16350 to prevent explosion risks in ATEX environments
- > Anti-static test result (palm, back, cuff): 1.73×10^4 Ohms, 2.31×10^3 Ohms, 2.98×10^2 Ohms
- > Contact heat resistance 1 (100 °C for at least 15 seconds)
- > Touch-screen suitable

APPLICATION

- > Precision handling of sharp and abrasive pieces, also in presence of light contact heat risk in automotive, aerospace, mechanical, metal, glass and maintenance industry
- > ATEX environments (explosive gases, vapours, mists and dusts) such as chemical and energy industry, wheat, flour or sugar silos, sawmills
- > Suitable for product protection in EPA environments (ESD Protected Area) in the electronical industry and other industries involving electronical components

CAT	CAT.II
Environment	Dry or slightly wet/oily
Construction	Seamless knitted
Gauge	18
Coating area	Palm
Length (mm)	220-270
Cuff type	Elasticized knitted wrist
Ambidextrous	No
Material	High tenacity elasticized HPPE/polyamide/spandex yarn with Soft-Shield technology
Size	6-11
Packing	Box: 144 PA Sales Units: 12 PA



Release 21/03/2024

REGISTRATED TRADEMARK SAFETY SYSTEM
(DEP.NUM. 302017000074272)



Lanzi SRL Via Giulio Natta, 27/A Torino - Italia
Tel: +39 011 2284011 - Fax: +39 011 2884022
contact@lanzigroup.com